



# MATERIAL SAFETY DATA SHEET

## SSP-12000 B ANTI GRAFFITI ACTIVATOR

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: SHOP SMART  
Phone Number: 1-310-405-6423  
Emergency Phone: 1-800-424-9300 (CHEMTREC)  
Product Name: SSP-12000 B ANTI GRAFFITI ACTIVATOR  
Product Number: SSP-12000 B  
Prepared By: Safety Manager  
Date Prepared: 08/29/2008  
Synonyms:  
Web Site: [www.sspproducts.com](http://www.sspproducts.com)

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name               | CAS        | OHSA PEL                | ACGIH TLV | Weight %  |
|-----------------------------|------------|-------------------------|-----------|---|
| BUTYL ACETATE               | 123864     | PEL = 150 ppm(710mg/M3) |           | STEL = 200 ppm(950 mg/M3) TLV = 150ppm(713 mg/M3) |
| XYLENE                      | 1330207    | PEL = 100 ppm(435mg/M3) |           | STEL = 150 ppm(651 mg/M3) TLV = 100ppm(434 mg/M3) |
| ACETONE                     | 67641      |                         |           |   |
| HI-SOL 10                   | 64742-95-6 |                         |           |   |
| HEXAMETHYLENE DI-ISOCYANATE | 822060     |                         | N/A       | TLV = 0.005ppm(0.034 mg/M3)                       |
| PM-ACETATE                  | 108656     | N/A                     | N/A       | 100   |
| OXSOL-100                   | 98566      |                         |           |   |

### 3. HAZARDOUS IDENTIFICATION

Emergency Overview: N/A

#### POTENTIAL HEALTH EFFECTS

Eye Contact: Contact causes severe irritation and pain associated with redness and swelling of the conjunctive.

Inhalation: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting, and malaise.

Ingestion: Moderately toxic; may cause headache, dizziness, diarrhea and general weakness; large doses may result in red blood cell hemolysis. Aspiration of minute amounts of vomit into lungs may produce severe lung injury or death.

Skin Contact: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis. CURED MATERIAL IS HARD TO REMOVE.

Signs And Symptoms Of Exposure: N/A

### 4. FIRST AID MEASURES

Eye Contact: Flush eyes with water for 15 minutes while holding eyelids open; if irritation persists seek medical attention.

Inhalation: Remove victim to fresh air; provide oxygen if breathing is difficult; administer CPR if victim is not breathing; seek medical attention.

Ingestion: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Skin Contact: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Aggravated Medical Conditions: N/A

Supplemental Health Information: N/A

## **5. FIRE FIGHTING MEASURES**

### **FLAMMABLE PROPERTIES**

Flash Point: -4

Flash Point Method: 76 Fahrenheit

Autoignition: N/A

LEL: 2

UEL: 11.5

Extinguishing Media: Co2; Water Fog, Dry Chemical; Chemical Foam

Special Fire-Fighting Procedures: Firefighters must wear full facepiece self-contained apparatus in positive pressure mode. Do not use solid stream of water since stream will scatter and spread fire. Fine water spray can be used to keep fire-exposed containers cool.

Unusual Fire And Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat; do not use direct stream of water on pool fires as product may reignite on water surface. Caution- Material is Flammable.

Combustion Products: N/A

## **6. ACCIDENTAL RELEASE MEASURES**

Steps To Be Taken In Case Material Is Spilled Or Released: Small spills: Mop up, wipe up or soak up immediately. Remove to out of doors. Large spills: Evacuate area. Contain liquid; transfer to closed metal containers. Keep out of water supply.

## **7. HANDLING AND STORAGE**

Precautions To Be Taken In Handling And Storage: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Caution flammable-Keep away from all sources of ignition. Empty containers may contain residue which may form explosive vapors. Do not weld or cut near empty container that has not been professionally reconditioned. Use NOS-SPARKING tools when opening and closing containers. Maintain well work areas to minimize exposure when handling this material.

Other Precautions: In case material is released or spilled: Caution-Flammable! Evacuate and ventilate area; confine and absorb into absorbent; place material into approved containers for disposal; for spills in excess of allowable

limits (RQ) notify the national response center (800) 424-8802; refer to cercla 40 CFR 302 and SAARA TITLE #, section 313 40 CFR 372 for detailed instructions concerning reporting requirements.

## **8. EXPOSURE CONTROL / PERSONAL PROTECTION**

### **PERSONAL PROTECTIVE EQUIPMENT**

Respiratory Protection: None required while threshold limits (section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn.

Ventilation: Local exhaust: required/mechanical yes

Protective Gloves: Neoprene or rubber

Eye Protection: Goggles with side shields; safety eye bath nearby.

Other Protective Clothing or Equipment: Coveralls, apron, or other equipment should be worn to minimize skin contact.

Work/Hygienic Practices: Practice safe workplace habits. Minimize body contact with this as well as all chemicals in general.

Engineering Controls: N/A

Exposure Guidelines: N/A

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance And Odor: Clear, Aromatic Odor

Solubility In Water: Negligible

Boiling Point: 350.38

Vapor Pressure: 73 mm @ 20 C

Specific Gravity: 0.902

Melting Point: N/A

Freezing Point: N/A

Evaporation Rate: Heavier Than Air

Vapor Density: Heavier Than Air

Percent Volatile: 51%

Ph: N/A

Molecular Weight: N/A

Pounds Per Gallon: 0

Other Properties: N/A

## **10. STABILITY AND REACTIVITY**

Stability: Stable

Conditions To Avoid: Extreme temperatures, sparks and flames.

Incompatibility: Strong oxides and acids

Hazardous Decomposition Or By Products: Thermal decomposition may yield CO; CO2

Hazardous Polymerization: Will Not Occur

Conditions To Avoid: Avoid heat, flame, and other sources of ignition.

## **11. TOXICOLOGICAL INFORMATION**

N/A

## **12. ECOLOGICAL INFORMATION**

N/A

## **13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local, state, and federal regulations. This product may produce concentrated hazardous vapors or fumes in a disposal container creating a dangerous environment. Refer to "40 cfr protection of environment parts 260299" for complete waste disposal regulations for ignitable materials. consult your local, state, or federal environment protection agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

## **14. TRANSPORT INFORMATION**

DOT Class: Paint Related Material

Hazard Class: 3

UN No.: UN 1263

Packing Group: III

Guide No: 60

Ship Name: Paint Related Material

## **15. REGULATORY INFORMATION**

N/A

## **16. OTHER INFORMATION**

Health: 2

Flammability: 3

Reactivity: 1

Protective:

OTHER ADDITIONAL INFORMATION: