

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 001  
Date Prepared: 07/12/06  
Date Printed: 10/02/06  
MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: ANTI-STATIC FINAL WIPE SSP 6000  
General or Generic ID: SOLVENT BLEND

Company

SHOPSMART SUPPLY  
3535 ROSECRANS AVENUE  
HAWTHORNE CA 90250  
1-877-644-1333

Emergency Telephone Number:

CHEMTREC.  
1-800-424-9300  
24 HOURS EVERYDAY

---

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by volume)
ISOPROPANOL	67-63-0	98.0-100.0

---

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury. Exposure causes severe irritation of the gastrointestinal tract.

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 002

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), low blood pressure, mild, temporary changes in the liver, effects on heart rate, respiratory depression (slowing of the breathing rate), loss of coordination, confusion, lung edema (fluid buildup in the lung tissue), kidney damage, coma.

Target Organ Effects

Breathing isopropanol vapors has caused damage to the lining of the middle ear in experimental animals. The relevance of this finding to humans is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 003  
Date Prepared: 07/12/06  
Date Printed: 10/02/06  
MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

Other Health Effects  
No data

Primary Route(s) of Entry  
Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

---

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Pulmonary edema may be delayed. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidney, Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver toxicity in experimental animals.

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 004

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

5. FIRE FIGHTING MEASURES

Flash Point

53.0 - 63.0 F (11.6 - 17.2 C) TCC

Explosive Limit

(for component) Lower 2.0 Upper 12.0 %

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

alcohol resistant (AR) foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

NFPA Rating

Health - 2, Flammability - 3, Reactivity - 0

---

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 005

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).

---

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 006  
Date Prepared: 07/12/06  
Date Printed: 10/02/06  
MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

Storage

Do not store near extreme heat, open flame, or sources of ignition.

---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

-----

ISOPROPANOL (67-63-0)  
OSHA PEL 400.000 ppm - TWA  
OSHA VPEL 400.000 ppm - TWA  
OSHA VPEL 500.000 ppm - STEL  
ACGIH TLV 200.000 ppm - TWA  
ACGIH TLV 400.000 ppm - STEL

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 007

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) 180.0 F (82.2 C)

Vapor Pressure

(for component) 33.000 mmHg

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

.770 - .802 @ 68.00 F

Liquid Density

6.550 lbs/gal @ 68.00 F

.786 kg/l @ 20.00 C

Percent Volatiles

No data

Volatile Organic Compounds (VOC)

784.500 g/l

Evaporation Rate

SLOWER THAN ETHYL ETHER

Appearance

FREE OF SUSPENDED MATTER

State

LIQUID

Physical Form

HOMOGENEOUS SOLUTION

Color

WATER WHITE

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 008

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

Odor

HYDROCARBON

pH

No data

---

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: acids, aldehydes, alkalis, amines, chlorinated hydrocarbons, ethylene oxide, halogens, isocyanates, strong oxidizing agents, Do not use with aluminum equipment at temperatures above 120 degrees F.

---

11. TOXICOLOGICAL INFORMATION

No data

---

12. ECOLOGICAL INFORMATION

No data

---

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 009

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-531-7106.

---

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

FLAMMABLE LIQUID, N.O.S., 3, UN1993, II

Container/Mode:

55 GAL DRUM/TRUCK PACKAGE

NOS Component:

Not applicable

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

Other Transportation Information

The Transport Information may vary with the container and mode of shipment.

---

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 010

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

CERCLA RQ - 40 CFR 302.4(a)  
None listed

SARA 302 Components - 40 CFR 355 Appendix A  
None

Section 311/312 Hazard Class - 40 CFR 370.2  
Immediate(X) Delayed(X) Fire(X) Reactive( ) Sudden  
Release of Pressure( )

SARA 313 Components - 40 CFR 372.65  
None

OSHA Process Safety Management 29 CFR 1910  
None listed

EPA Accidental Release Prevention 40 CFR 68  
None listed

International Regulations  
Inventory Status  
Not determined

State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.

1,4-DIOXANE  
ETHYLENE OXIDE

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.

ETHYLENE OXIDE

New Jersey RTK Label Information  
ISOPROPYL ALCOHOL

67-63-0

Continued on next page

MATERIAL SAFETY DATA SHEET

SHOPSMART SUPPLY

Page 011

Date Prepared: 07/12/06

Date Printed: 10/02/06

MSDS No: 301.0411787-001.001

ANTI-STATIC FINAL WIPE SSP 6000

---

Pennsylvania RTK Label Information  
2-PROPANOL

67-63-0

---

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.